



MADE OF TRUST



# ***YOUR PERFECT PARTNER FOR WORK***



## ***ECO 150 CARGO***

# ECO 150 CARGO

## SPECIFICATIONS

<b>Engine</b>	Maximum power	10 kW (13.4 BHP) @ 8000 rpm
	Maximum torque	12.80 N-m @ 5000 rpm
	Bore and stroke	57.3x.57.8 mm
	compression ratio	9.1:1
	Displacement	149.1 cc
	Spark plug	NGK-cPR 8 EA9, cHAMPION-RG 6 Yc
	Spark plug gap	0.8-0.9 mm
	Spark plug gap	0.8-0.9 mm
	Valve clearance	0.08 mm
	Idle speed	1400 rpm
<b>Transmission</b>	Gearbox	5-Speed manual
<b>Suspension</b>	Front Suspension	Telescopic Hydraulic Shock Absorbers
	Rear Suspension	"Swingarm with adjustable Hydraulic shock absorber"
	caster angle	26°
	Trail length	89 mm
<b>Brake</b>	Front	Internal expanding shoe type (130 mm)
	Rear	Internal expanding shoe type (130 mm)
<b>Tyre</b>	Front	2.75x18-42P/4PR
	Rear	3.00x18-52P/6PR
<b>Electricals</b>	Battery	12V-7Ah
	Alternator	125 W
	Starting system	Electric start
	Headlamp (High/Low)	12V-35/35W Halogen Bulb-*MFR
	Tail/Stop lamp	12V-5/21W-*MFR
	Turn signal lamp	12V-10Wx4-*MFR
	Meter illumination	12V-1.7Wx3
	Neutral indicator	12V-1.7W
	Turn signal indicator	12V-3.0Wx2
	Position lamp	12V-3.0W
Hi Beam indicator	12V-1.7W	
<b>Dimensions</b>	Overall length	2061 mm
	Overall width	763 mm
	Overall height	1100 mm
	Wheelbase	1290 mm
	Ground clearance	160 mm
<b>Weights</b>	Kerb weight	140 kg (Self)
	Maximum payload	130 kg