SPECIFICATIONS

Frame

Clutch

Transmission

Engine Type

Displacement **Maximum Power Maximum Torque Bore x Stroke Compression Ratio** Starting **Fuel Supply**

Air cooled, 4 Stroke 2 Valve Single cylinder, OHC 199.6 cc 13.5kw/18.1 bhp @ 8000 rpm 17.1 Nm @ 6500 rpm 66.5mm X 57.5mm 10:01 **Electric and Kick** FL

Diamond Muli-plate wet clutch 5-speed constant mesh gear

Front		
Rear		

Front Rear

WHEELS & TYRES

Front Rear

Telescopic front forks (37mm Battery Dia) with antifriction bush Headlamp Rectangular swingarm with Tail/ Stop Lamp adjustable mono-shock Turn Signal Lamp

12V-6 Ah, (ETZ-7) MF Battery 12V-5.6W/9.3W (LED) 12V-0.2/2.1W (LED) 12V-10Wx4 MFR (Amber bulb with clear lens)

Length x Width x Height	2222 x 850 x 1258 mm		
Wheelbase	1410 mm		
Ground Clearance	220 mm		
Fuel Tank Capacity	13 Liter		
Kerb Weight	154KG		



200CC HIGH TORQUE FI ENGINE



STYLISH UPSWEPT EXHAUST



Disc Dia. 276 mm

Disc Dia. 220 mm

90/90-21 M/C 54S

120/80-18 M/C 62S

TURN BY TURN NAVIGATION



USB CHARGER



10 Step Adjustable . Monosĥock





BORN FOR THE TOUGHEST TERRAINS

ADVANCE





На него