

 Hero

अटुट विश्वास
हरेक यात्रामा



Splendor+

 CG MOTORS

Splendor+

SPECIFICATIONS

Engine	Engine Type	Air cooled, 4 - Stroke Single Cylinder OHC
	Displacement	97.2 cc
	Maximum Power	6.15 kW (8.36 Ps) @ 8000 rpm
	Maximum Torque	0.82 Kgfm (8.05 Nm) @ 5000 rpm
	Bore x Stroke	50.0 x 49.5 mm
	Compression Ratio	9.9:1
	Starting	Kick start / Self start
Chassis & Transmission	Frame	Tubular Double Cradle Type
	Clutch	Multi-plate wet Type
	Transmission	4 Speed Constant Mesh
Suspension	Front	Telescopic Hydraulic Shock Absorbers
	Rear	Swing Arm with 5 Step Adjustable Hydraulic Shock Absorber
Brakes	Front	Internal Expanding Shoe Type (130 mm) - Non Asbestos type
	Rear	Internal Expanding Shoe Type (130 mm) - Non Asbestos type
Tyres	Front	2.75 X 18" M/C 42P (Tube)
	Rear	2.75 X 18" M/C 48P (Tube)
Electrical	Battery	12V-3 Ah MF (ETZ4)
	Head Lamp	12V - 35/35 W-Halogen Bulb (MFR)
	Tail/Stop Lamp	12V-5/10W (Multi-Focal Reflector)
Dimensions	Overall Length	2000 mm
	Overall Width	720 mm
	Overall Height	1040
	Wheelbase	1230 mm
	Ground Clearance	159 mm
Weights	Kerb Weight	112.3 kgs (Electric Start)
	Fuel Tank Capacity	11 Litres



i3s
टेक्नोलॉजी



एलॉय
व्हील्स



पावर
स्टार्ट



शक्तिशाली
हेडल्याम्प